


**M SORA**

okno je več kot pogled

**OKNA V LESU****NATURA****NATURA 3P****NATURA 3****NATURA +****PASIV****PASIV XPS****PASIV IZO****VIZIJA****Dimenzije profila (mm)**

Vgradna debelina

**68****68****68****102****68****118****140****68**

Vidna širina

**118****118****118****125****100****100****114****124****Vgradne oblike**

Pravokotne

•

•

•

•

•

•

•

•

Poševne

•

•

•

/

•

•

•

/

Ločne, polokrogle

•

•

•

/

•

•

/

/

**Načini odpiranja**

Fiksno

•

•

•

•

•

•

•

•

Kombinirano (d in dk)

•

•

•

•

•

•

•

•

Zložljive stene

•

/

•

/

/

/

/

/

Dršno-nagibne stene

•

/

•

•

•

•

•

•

Dvižno-dršne stene

•

•

•

/

•

•

•

•

Odpiranje navzven

•

•

•

•

/

/

/

/

Obojstranska pololiva

•

•

•

•

/

/

/

•

**Toplotna izolacija okna Uw (W/m<sup>2</sup>K)**

Ug = 1,1

**1,25**

/

/

/

/

/

/

**1,28**

Ug = 1,0

**1,19**

/

/

/

/

/

/

/

Ug = 0,9

**1,14**

/

/

/

/

/

/

/

Ug = 0,8

/

**1,05**

/

/

/

/

/

/

Ug = 0,7

/

**0,96****0,99****1,0** (ž. alu)

/

/

/

/

Ug = 0,6

/

**0,92****0,90**

/

**0,84****0,76****0,74**

/

Ug = 0,5

/

**0,84****0,86**

/

**0,77****0,69****0,65****0,83****Zvočna izolacija enokrlnih oken (dB)****33-36****33-42****33-44****33-44****33-43****33-43****34-44****32-36****Varnostno okovje**

WK1

•

•

•

•

•

•

•

•

Samo D in DK odpiranje, standardno vidno okovje

WK2

•

•

•

•

•

•

•

•

**Število tesnil**

Standardno

**2****2****2****2****3****3****3****2**

Opcija

**3****3****3****3**

/

/



/

**3***Pridružujemo si pravico do tehničnih in vsebinskih sprememb!*

# M SORA

okno je več kot pogled

## OKNA V KOMBINACIJI LESA IN ALUMINIJA



UDOBJE

UDOBJE 3

UDOBJE +

PRESTIŽ

POLAR E

POLAR

JAPAN

KLASIK

Dimenzije profila (mm)	Vgradna debelina	84	84	84	84	121	138	138	234
	Vidna širina	107	107	107	107	125	143	136	137
Vgradne oblike	Pravokotne	•	•	•	•	•	•	•	•
	Poševne	•	•	/	/	•	/	/	/
	Ločne, polokrogle	•	•	/	/	/	/	/	*samo nadsvetlobe
Načini odpiranja	Fiksno	•	•	•	/	•	•	/	/
	Kombinirano (d in dk)	•	•	•	•	•	•	•	•
	Zložljive stene	•	•	/	/	/	/	/	/
	Drsno-nagibne stene	•	•	•	/	/	•	/	•
	Dvižno-drsne stene	•	•	•	•	/	/	/	/
	Odpiranje navzven	•	•	/	/	/	/	/	/
	Obojestranska pololiva	•	•	•	/	/	/	/	/
Toplotna izolacija okna Uw (W/m2K)	Ug = 1,1	1,27	/	/	1,04	/	/	/	0,67
	Ug = 1,0	1,2	/	/	/	/	/	/	/
	Ug = 0,9	/	/	/	0,98	/	/	/	/
	Ug = 0,8	/	/	/	/	/	/	/	/
	Ug = 0,7	/	/	1,06 (ž, alu)	/	0,90 (ž, alu)	/	0,71	/
	Ug = 0,6	/	0,87	/	/	0,75	0,76	/	0,48
	Ug = 0,5	/	0,80	0,86 (ž, tgi)	/	0,69	0,66	0,62	/
Zvočna izolacija enokrilnih oken (dB)	33-36	33-42	33-42	39-40	33-44	33-44	43-46	37-47	
Varnostno okovje	WK1	•	•	•	•	•	•	•	•
	Samo D in DK odpiranje, standardno vidno okovje	WK2	•	•	•	/	•	•	/
Število tesnil	Standardno	2	2	3	2	3	4	4	2-2
	Opcija	3	3	/	3	4	/	/	3-2

Pridružujemo si pravico do tehničnih in vsebinskih sprememb!