









DRVENI PROZORI

									
		NATURA	NATURA 3P	NATURA 3	NATURA +	PASIV	PASIV XPS	PASIV IZO	VIZIJA
Dimenzije profila (mm)	Ugradna debljina	68	68	68	102	68	118	140	68
	Vidljiva širina	118	118	118	125	100	100	114	124
Oblici izvedbe	Pravokutne	•	•	•	•	•	•	•	•
	Kose	•	•	•	/	•	•	•	/
	Lučne, polukružne	•	•	•	/	•	•	/	/
Načini otvaranja	Fiksno	•	•	•	•	•	•	•	•
	Kombinirano (d in dk)	•	•	•	•	•	•	•	•
	Klizne stijene	•	/	•	/	/	/	/	/
	Otklopno-klizne stijene	•	/	•	•	•	•	•	•
	Podizno-klizne stijene	•	•	•	/	•	•	•	•
	Otvaranje na van	•	•	•	•	/	/	/	/
Poluoliva obostrano	•	•	•	•	/	/	/	•	
Toplinska izolacija prozora Uw (W/m²K)	Ug = 1,1	1,25	/	/	/	/	/	/	1,28
	Ug = 1,0	1,19	/	/	/	/	/	/	/
	Ug = 0,9	1,14	/	/	/	/	/	/	/
	Ug = 0,8	/	1,05	/	/	/	/	/	/
	Ug = 0,7	/	0,96	0,99	1,0 (z. alu)	/	/	/	/
	Ug = 0,6	/	0,92	0,90	/	0,84	0,76	0,74	/
	Ug = 0,5	/	0,84	0,86	/	0,77	0,69	0,65	0,83
Zvučna izolacija jednokrlnog prozora (dB)		33-36	33-42	33-44	33-44	33-43	33-43	34-44	32-36
Sigurnosni okovi	WK1	•	•	•	•	•	•	•	•
	Samo Z i OZ otvaranje, Standardno vidljivi okovi	WK2	•	•	•	•	•	•	•
Broj brtvi	Standardno	2	2	2	2	3	3	3	2
	Opcija	3	3	3	3	/	/	/	3

Pridružujemo si pravico do tehničnih in vsebinskih sprememb!