




DRVENI PROZORI

PASIV

PASIV XPS

PASIV IZO

Dimenzije profila (mm)	Ugradna debljina	68	118	140
	Vidljiva širina	100	100	114
Oblici izvedbe	Pravokutne	•	•	•
	Kose	•	•	•
	Lučne, polukružne	•	•	/
Načini otvaranja	Fiksno	•	•	•
	Kombinirano (d in dk)	•	•	•
	Klizne stijene	/	/	/
	Otklopno-klizne stijene	•	•	•
	Podizno-klizne stijene	•	•	•
	Otvoranje na van	/	/	/
	Poluoliva obostrano	/	/	/
Toplinska izolacija prozora Uw (W/m2K) 	Ug = 1,1	/	/	/
	Ug = 1,0	/	/	/
	Ug = 0,9	/	/	/
	Ug = 0,8	/	/	/
	Ug = 0,7	/	/	/
	Ug = 0,6	0,84	0,76	0,74
	Ug = 0,5	0,77	0,69	0,65
Zvučna izolacija jednokrlnog prozora (dB)			33-43	34-44
SIGURNOSNI OKOVI Samo Z i OZ otvaranje, Standardno vidljivi okovi	WK1	•	•	•
	WK2	•	•	•
Broj brtvi	Standardno	3	3	3
	Opcija	/	/	/