



PROZORI U KOMBINACIJI DRVO ALUMINIJ

POLAR

POLAR E

POLAR E92

POLAR E122

Dimenzije profila (mm)	Ugradna debljina	138	121	92	122
	Vidljiva širina	143	125	110	110
Oblici izvedbe	Pravokutne	•	•	•	•
	Kose	/	•	•	•
	Lučne, polukružne	/	/	•*	•*
Načini otvaranja	Fiksno	•	•	•	•
	Kombinirano (d in dk)	•	•	•	•
	Klizne stijene	/	/	•*	•*
	Otklopno-klizne stijene	•	/	•	•
	Podizno-klizne stijene	/	/	•	•
	Otvoranje na van	/	/	•*	•*
	Poluoliva obostrano	/	/	•*	•*
Toplinska izolacija prozora U_w (W/m ² K)	U _g = 1,1	/	/	/	/
	U _g = 1,0	/	/	/	/
	U _g = 0,9	/	/	/	/
	U _g = 0,8	/	/	/	/
	U _g = 0,7	/	0,90 (ž, alu)	/	/
	U _g = 0,6	0,76	0,75	/	/
	U _g = 0,5	0,66	0,69	0,70	0,68
	Zvučna izolacija jednokrlnog prozora (dB)	33-44	33-44	33-44	33-44
SIGURNOSNI OKOVI	WK1	•	•	•	•
	Samo Z i OZ otvaranje, Standardno vidljivi okovi	WK2	•	•	•
Broj brtvi	Standardno	4	3	3	3
	Opcija	/	4	/	/

•* Izolacijski del je poln smrekov les brez zračnih rež

POLAR E92, POLAR E122 - prve dobave predvidoma septembra 2010