









## DRVENI PROZORI

									
		NATURA	NATURA 3P	NATURA 3	NATURA +	PASIV	PASIV XPS	PASIV IZO	VIZIJA
<b>Dimenzije profila (mm)</b>	Ugradna debljina	68	68	68	102	68	118	140	68
	Vidljiva širina	118	118	118	125	100	100	114	124
<b>Oblici izvedbe</b>	Pravokutne	•	•	•	•	•	•	•	•
	Kose	•	•	•	/	•	•	•	/
	Lučne, polukružne	•	•	•	/	•	•	/	/
<b>Načini otvaranja</b>	Fiksno	•	•	•	•	•	•	•	•
	Kombinirano (d in dk)	•	•	•	•	•	•	•	•
	Klizne stijene	•	/	•	/	/	/	/	/
	Otklopno-klizne stijene	•	/	•	•	•	•	•	•
	Podizno-klizne stijene	•	•	•	/	•	•	•	•
	Otvaranje na van	•	•	•	•	/	/	/	/
	Poluoliva obostrano	•	•	•	•	/	/	/	•
<b>Toplinska izolacija prozora Uw (W/m2K)</b>	Ug = 1,1	1,25	/	/	/	/	/	/	1,28
	Ug = 1,0	1,19	/	/	/	/	/	/	/
	Ug = 0,9	1,14	/	/	/	/	/	/	/
	Ug = 0,8	/	1,05	/	/	/	/	/	/
	Ug = 0,7	/	0,96	0,99	1,0 (ž, alu)	/	/	/	/
	Ug = 0,6	/	0,92	0,90	/	0,84	0,76	0,74	/
	Ug = 0,5	/	0,84	0,86	/	0,77	0,69	0,65	0,83
<b>Zvučna izolacija jednokrillnog prozora (dB)</b>		33-36	33-42	33-44	33-44	33-43	33-43	34-44	32-36
<b>Šigurnosni okovi</b>	WK1	•	•	•	•	•	•	•	•
	Samo Z i OZ otvaranje, Standardno vidljivi okovi	WK2	•	•	•	•	•	•	•
<b>Broj brtvi</b>	Standardno	2	2	2	2	3	3	3	2
	Opcija	3	3	3	3	/	/	/	3



## PROZORI U KOMBINACIJI DRVO ALUMINIJ

UDOBJE

UDOBJE 3

UDOBJE +

PRESTIŽ

POLAR E

POLAR

JAPAN

KLASIK

Dimenzije profila (mm)	Ugradna debljina	84	84	84	84	121	138	138	234
	Vidljiva širina	107	107	107	107	125	143	136	137
Oblici izvedbe	Pravokutne	•	•	•	•	•	•	•	•
	Kose	•	•	/	/	•	/	/	/
	Lučne, polukružne	•	•	/	/	/	/	/	*samo nadsvetlobe
Načini otvaranja	Fiksno	•	•	•	/	•	•	/	/
	Kombinirano (d in dk)	•	•	•	•	•	•	•	•
	Klizne stijene	•	•	/	/	/	/	/	/
	Otklopno-klizne stijene	•	•	•	/	/	•	/	•
	Podizno-klizne stijene	•	•	•	•	/	/	/	/
	Otvaranje na van	•	•	/	/	/	/	/	/
	Poluoliva obostrano	•	•	•	/	/	/	/	/
Toplinska izolacija prozora Uw (W/m2K)	Ug = 1,1	1,27	/	/	1,04	/	/	/	0,67
	Ug = 1,0	1,2	/	/	/	/	/	/	/
	Ug = 0,9	/	/	/	0,98	/	/	/	/
	Ug = 0,8	/	/	/	/	/	/	/	/
	Ug = 0,7	/	/	1,06 (ž, alu)	/	0,90 (ž, alu)	/	0,71	/
	Ug = 0,6	/	0,87	/	/	0,75	0,76	/	0,48
	Ug = 0,5	/	0,80	0,86 (ž, tgi)	/	0,69	0,66	0,62	/
Zvučna izolacija jednokrlnog prozora (dB)	33-36	33-42	33-42	39-40	33-44	33-44	43-46	37-47	
Sigurnosni okovi	WK1	•	•	•	•	•	•	•	•
	WK2	•	•	•	/	•	•	/	/
Broj brtvi	Standardno	2	2	3	2	3	4	4	2-2
	Opcija	3	3	/	3	4	/	/	3-2

Pridružujemo si pravico do tehničnih in vsebinskih sprememb!